

## Reference Station Receiver



- Super Low Power Consumption
- 144 Universal Channel Satellite Tracking
- Superior Signal Tracking and Performance
- 100Hz Selectable Data Update Rate
- Up to 32GB memory card for data storage

## Advanced Reference Station Receiver

Using a unique patented technology, the NET-G3A incorporates 144 Universal Tracking Channels, capable of tracking all GPS and GLONASS satellites.

With the incorporation of GPS, GPS L2C and L5, as well as Glonass; Topcon offers the ultimate network receiver solution,



providing the very best reference station solution for your network users. When used with its companion, the CR-G5 choke ring antenna, the NET-G3A is the ultimate reference station solution. The NET-G3A boasts complete system connectivity. USB, Ethernet, and four serial ports combined with an industry leading 100Hz data rate, the NET-G3A offers high speed connections both in and out of the reference station.

Two new features have been introduced in the NET-G3A receiver: USB Host and HTML Web User Interface. The USB Host feature allows the user to connect a USB memory stick or USB Mass Storage Device (UMS) to the NET-G3A receiver. The UMS provides a sleek and high-capacity storage solution for transferring raw data files from the receiver's CF card. The NET-G3A also includes a built-in Web server that allows the user to configure and monitor the receiver via a Web user interface (or Web interface). The built-in Web server and Web interface use HTTP/HTTPS protocols for communication.

Offer network users a complete signal solution – the new NET-G3A. Only from Topcon, the World leader in advanced positioning technologies.



7400 National Drive • Livermore • CA 94550  
(925) 245-8300

Specifications subject to change without notice. ©2013 Topcon Corporation  
All rights reserved. P/N: 7010-2027 Rev. B TF Printed in U.S.A. 2/13

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

## SPECIFICATIONS

### Tracking

Number of Channels	144 Universal Channels
Signals Tracked	GPS L1, L2, & L5 carrier, CA, L1 P, L2 P, L2C GLONASS L1, L2, & L5 carrier, L1CA, L2CA, L1 P, L2 P
WAAS/EGNOS	Yes
Antenna Type	CR-G5 Choke ring, G3-A1 Geodetic, PN-A5 Full Spectrum GNSS Antenna

### Accuracy

Real time RTK accuracy	H: 10mm+1ppm V: 15mm+1ppm
Post processed Static	H: 3mm+0.5ppm V: 5mm+0.5ppm

### Data & Memory

Internal Memory	None
Additional Memory	Removable CF Memory Card up to 32GB* and USB Host that allows the ability to plug in a USB memory stick or a USB mass storage device
Data Update/Output Rate	1-100Hz Selectable
Real Time Data Output	TPS, RTCM SC104 ver 2.1, 2.2, 2.3, and 3.0, CMR, CMR+, BINEX
ASCII Output	NMEA 0183 version 2.1, 2.2, 2.3, 3.0 and 3.01
Other I/O Signals	1pps, Event Marker, External Frequency input, 20 MHz frequency output
Control & Display Unit	GUI external software interface

### Communications

TCP/IP Address	Up to 5 different address ports standard
NTRIP	Client and Server functionality
Ports	4 Serial, 1 USB, 2 Power, 1 Ethernet
HTML Web User Interface	Web User Interface access via Internet - Explorer, Firefox, and Opera

### Physical Characteristics

Status Indicators	6x3 color LED's
User Interface	2 Key
Dimensions	(W x H x L) 166mm x 93mm x 275mm 6.54" x 3.66" x 10.83"
Weight	3.0 kg (6.61 lbs)

### Power

Internal Power	2 Lithium Ion batteries 7.4 Volts, 6000 mA-hr
External Power Input	6 to 28 Volts DC
Typical Power Consumption	Less than 4.5 Watts
Power Ports	2, 1 primary, 1 secondary

### Environmental

Enclosure	Aluminum
Operating Temperature	-40°C to 65°C
Storage Temperature	-40°C to 75°C
Environmental Specification	IP67 waterproof/dustproof, MIL-STD 810F

\* Firmware version 4.0 or newer is required

Your local Authorized Topcon dealer is: